

Presses

HDDT-100

HDDT-200

HDDT-300

HDDT-400

HDDT-500

HDDT-600

Technical specifications

Force [tn]:	100	200	300	400	500	600
Motor power [kw]:	22	22	22	30	30	37
Working speed [mm/sec]:	15	8	10	10	8	15
Approaching speed [mm/sec]:	100	100	100	100	100	100
Return speed [mm/sec]:	140	140	140	140	140	110
Piston stroke [mm]:	1000	1000	1000	1000	1000	1000
Table size [mm]:	800 x 1000	800 x 1000	1000 x 1200	1200 x 1400	1200 x 1500	1500 x 1700
Max. day light [mm]:	1000	1000	1000	1000	1000	1000
Hydraulic cushion [tn]:	40	65	130	150	200	250
Hydraulic cushion stroke [mm]:	300	300	300	300	300	300
Total length [mm]:	2200	2200	2400	2600	2600	3000
Total width (frontal) [mm]:	2100	2100	2300	2500	2500	2800
Overall height [mm]:	4100	4200	4500	4700	4900	5500
Weight [kg]:	9000	12000	17000	23000	26000	33000

Features

Chrome Plated Cylinder	•	•	•	•	•	•
Steel Welded Frame	•	•	•	•	•	•
T-slotted tables (DIN 508/650)	•	•	•	•	•	•
Main Cylinder & Hydraulic Cushion	•	•	•	•	•	•
Light Curtains (Frontal)	•	•	•	•	•	•
HMI Touch Screen Control	•	•	•	•	•	•
Programmable Pressure, Stroke, Time	•	•	•	•	•	•
Lubrication System	•	•	•	•	•	•
Oil Pressure Gauge	•	•	•	•	•	•
Palm Button Operation	•	•	•	•	•	•