

	PPE-30	PPE-40	PPE-4-40	PPE-4-60	PPE-4-80	PPE-4-100	PPE-4-125	PPE-4-160	PPE-4-200	PPE-4-250	PPE-4-315
							PPE-6-125	PPE-6-160	PPE-6-200	PPE-6-250	PPE-6-315
Technical Specifications											
Pressure force [tn]:	30	40	40	60	80	100	125	160	200	250	315
Guided Ram [qty]:	n/a	n/a	4	4	4	4	4 / 6	4 / 6	4 / 6	4 / 6	4 / 6
Motor power [kw]:	2,2	3	3	4	6	8	11	11	15	19	22
Throat depth [mm]:	180	220	220	235	250	280	300 / 325	350	400	450	450
Strokes per minute [spm]:	125	125	60	60	60	50	50 / 55	45 / 50	40 / 45	40 / 45	35 / 40
Stroke adjustment [mm]:	10 – 75	10 to 90	10 to 90	10 to 100	10 to 115	10 to 135	10 to 135	20 to 150	20 to 170	20 to 180	20 to 200
Max. closed mould height [mm]:	225	250	250	270	285	315	315	350	430	420	400
Distance between table and ram [mm]:	300	340	340	370	400	450	450	500	600	600	600
Ram adjustment [mm]:	50	50	50	50	50	60	60	70	80	80	90
Table size [mm]:	360 x 560	440 x 640	440 x 640	470 x 700	500 x 750	560 x 860	600 x 900 / 650 x 1000	700 x1100	800 x 1200	900 x 1200	900 x 1200
Ram size [mm]:	260 x 340	280 x 380	280 x 380	310 x 410	340 x 440	420 x 520	315 x 550 / 460 x 700	370 x 620 / 520 x 700	400 x 700 / 550 x 760	400 x 700 / 600 x 900	400 x 700 / 620 x 900
Table height [mm]:	670	670	670	670	700	800	800 / 900	950 / 920	950 / 1000	950 / 1000	950 / 1000
Ø hole in the table [mm]:	140	170	170	190	220	250	250 / 260	280	300	310	320
Ø hole in the ram [mm]:	35	40	40	40	45	50	50	55	60	65	70
Total width (frontal) [mm]:	1100	1300	1220	1230	1400	1630	1650 / 1800	1860 / 1950	2130 / 2280	2200 / 2270	2280 / 2270
Total length [mm]:	1300	1400	1370	1460	1500	1640	1680 / 1760	1800 / 1950	2100 / 2200	2100 / 2200	2150 / 2200
Overall height [mm]:	2000	2000	2200	2350	2500	2760	2870 / 3150	3200 / 3350	3250 / 3750	3280 / 3750	3450 / 3800
Features											
Central Motorized Lubrication	•	•	•	•	•	•	•	•	•	•	•
Hydraulic Overload Protection	•	•	•	•	•	•	•	•	•	•	•
Electro-pneumatic clutch / brake combo	•	•	•	•	•	•	•	•	•	•	•
Clutch Dual Safety Solenoid Valve	•	•	•	•	•	•	•	•	•	•	•
Comp. Tank, Reg.-lube Filter,Pressure Control	•	•	•	•	•	•	•	•	•	•	•
Sid screens w/Safety light guards	•	•	•	•	•	•	•	•	•	•	•
Programmable control system (PLC)	•	•	•	•	•	•	•	•	•	•	•
Adjustable stroke	•	•	•	•	•	•	•	•	•	•	•
Anti-vibration pads	•	•	•	•	•	•	•	•	•	•	•
Palm Button / Foot pedal Controls	•	•	•	•	•	•	•	•	•	•	•
Optional accessories											
Ejector Pneumatic / Hydraulic	•	•	•	•	•	•	•	•	•	•	•
Cushion Pneumatic / Hydraulic	•	•	•	•	•	•	•	•	•	•	•
Lower auxiliary table	•	•	•	•	•	•	•	•	•	•	•
Bespoke Dimensions	•	•	•	•	•	•	•	•	•	•	•
Strain gauge system	•	•	•	•	•	•	•	•	•	•	•
NC digital display with memories	•	•	•	•	•	•	•	•	•	•	•
     											