

Punching Machine



The RHTC Profi Punch, 16-ton machine, can not only be used as a punching machine but also as a small C-Frame press. It comes with a 2.2 kW motor and has a working speed range from 2 mm/s up to 9.8 mm per second and a returning speed of 20 mm/s. The stroke of the machine is controlled with the top and bottom guides on the front of the

The Profi Punch 16 has a variety of standard optional tools available which are available directly from the warehouse. These tools include corner notching, round and square, rod cutting, and tube drain hole punch. Other custom tools are available.

As with the rest of the machinery designed and manufactured by RHTC the Profi Punch machines are manufactured using the most recent and current CE regulations and directives and is delivered directly from the warehouse with a – year warranty and a CE certificate.

Profi Punch 16 Ton

Technical Specifications

Force (tons)	16
Motor (kw)	2.2
Min. working speed (mm/sec)	2.0
Max. working speed (mm/sec)	9.8
Return speed (mm/sec)	20
Piston Stroke (mm)	70
Throat depth (mm)	160
Total Length (mm)	800
Total width (mm)	450
Total height (mm)	1430
Weight (kg)	350

- Punch up to 4 mm mild steel
- Manual/Automatic modes
- 1600 punches/hr auto mode
- Pressure switch and manometer
- Foot pedal control
- Built in Europe
- CE Certified

Optional Accessories



Sheet Corner Notcher



Sheet Corner Notcher



Square Slot Notcher



Round Pipe Notcher



Square Tube Notcher



Rod Cutter