





-  Welding unit with inverter technology piloted by microprocessor.
-  The arc dynamic of the product is unique and revolutionary on the market.
-  Can be used with all types of electrodes: rutile, stainless steel, cast iron in direct current.
-  Very handy, thanks to its small weight (2.5 kg), its highly reduced volume and its very low consumption (plug 10A with AM fuse)




MMA

- ✓ **Immediate start** thanks to its very high no-load voltage.
- ✓ Constant welding **power**.
- ✓ **Very smooth melting** due to the direct current.
- ✓ **Insensate to supply current fluctuations** or to the arc length.
- ✓ **Very good penetration** and perfect arc stability.



Delivered in cardboard with (ref. 029958) :

- Earth cable (1.6m / $\varnothing 10\text{mm}^2$)
- Electrode holder (1.6m / $\varnothing 10\text{mm}^2$)



Delivered in suitcase with (ref. 029941) :




- Earth cable (1.6m / $\varnothing 10\text{mm}^2$)
- Electrode holder (1.6m / $\varnothing 10\text{mm}^2$)
- Hand mask
- Chipping hammer

ASSETS

HOT START : Increased power at start.

ANTI STICKING : Prevents the electrode sticking.

ARC FORCE : Instantaneous increase of the current in difficult welding situation.

50/60hz	+AM+	I ₂ MMA	 MINI 20"					EN60974-1 (40°C)		U ₀	 mm ²	cm/kg	 Protected & compatible POWER GENERATOR (+/- 15%)
			$\varnothing 1,6$	$\varnothing 2,0$	$\varnothing 2,5$	$\varnothing 3,2$	$\varnothing 4,0$	I _A (60%)	X% (I ₂ max)				
230V	10A	10 - 80A	62	50	20	-	-	31A	80A 6%	85V	10/25	10x14x23 / 2.5	3 kW 3.7 kVA