

GYSMI 130P

- Welding unit with inverter technology piloted by microprocessor.
- The arc dynamic of the product is unique and revolutionary on the market.
- Can be used with all types of electrodes: rutile, basic, stainless steel, cast iron in direct current.
- Very handy, thanks to its small weight (2.9 kg), its highly reduced volume and its very low consumption.

■ MMA

- ✓ Immediate start thanks to its very high no-load voltage
- ✓ Constant welding power
- ✓ Very smooth melting due to the direct current.
- ✓ Insensate to supply current fluctuations or to the arc length.
- ✓ Very good penetration and perfect arc stability.

■ ASSETS


- ✓ **ARC FORCE** : punctual increase of current in difficult welding situation.
- ✓ **HOT START** : increased power at start
- ✓ **ANTI STICKING** : anti sticking process.

130
A8 mm
max

1.6 3.2

Mini : 4 kW
(5 kVA)
Protected & Compatible

LCD TECHNO 11

 **High quality LCD:** UV/IR DIN 15 protection
Field of vision : 98 x 35 mm

 **Total weight:** 400 g

 **Power supply:** Solar

Filter:

- Initial shade : 3
- Welding shade: 11
- Arcing reaction time ≤ 0.6 ms
- Ideal for MMA/MIG-MAG/TIG : from 10 to 200 A



Ref. 031449

Delivered in bundle with:

- Earth cable (1,6m/ø16mm²)
- Electrode holder (2m/ø16mm²)
- Techno 11 helmet



Ref. 029972

Delivered in suitcase with:

- Earth cable (1,6m/ø16mm²)
- Electrode holder (2m/ø16mm²)

50/60hz	AM	I ₂	min>max	ø1.6	ø2	ø2.5	ø3.2	ø4	ø5	EN60974-1 (40°C)	U ₀	cm/kg	Protected & compatible POWER GENERATOR (+/- 15%)
230V 1~	13A	10-130A	20-200A	62	50	47	24	-	-	I _A (60%) 45A X% (I ₂ max) 5%	80V	10x17x25 2.9	4 kW 5.0 kVA