











Bandsaw

Mechanism for the rotation of bow unit together with circular support table for angled cuts up to 60° left and 45° right with locking lever. Manual vice with rapid approach: can be positioned lengthwise along the entire machine base

- Bow tilting on bearings with tapered rollers
- Double balancing springs on bow
- Safety switch for blade drive on lever hand grip
- Lockable mains switch
- Emergency pushbutton on pedestal
- Blade lubrication-cooling system with electric pump
- Coolant liquid tank with extractable pump for tank cleaning
- Protection guard on part of blade not directly involved in cutting
- Safety micro-switch on opening off flywheel cover
- Spring action band tightening device
- Blade guiding arm adjustable according to the dimensions of the pieces to be cut
- Bar stop with millimetric bad.

SN 300

		45°	0°	45°	60°
CUTTING CAPACITY	 mm	160	220	200	130
	 mm	120	190	150	110
	 mm	160 x 130	330 x 150	160 x 130	110 x 110
	 kW	1.25 / 1.75			
	 m/1'	35 / 70			
	 mm	360			
	 mm	2825 x 27.0 x 0.9			
	 kg	430			
	 mm	950			
	 mm	1400 x 1500 x 1800			

TECHNICAL SPECIFICATIONS

SN 300MRM
Version with manual clamp

SN 300NEWTON
Gravity feed version

