

Grinder Model	1600	1600X	50	50X	75	75X	75X Silverstar	100	100X	150	150X
Article number	416708110	416708210	430231120	430231220	430232130	430232230	439232230	430233140	430233240	430234140	430234240
Technical Specifications											
On Pedestal	•	•	•	•	•	•	•	•	•	•	•
Belt speed (m/sec)	28 / 33	28 / 33	30	30	30	30	30	30	30	30	30
Exhaust (m³/h)	--	--	--	630	--	630	630	630	630	--	630
Belt Width (mm)	50	50	50	50	75	75	75	100	100	150	150
Belt Length (mm)	1600	1600	2000	2000	2000	2000	2000	2000	2000	2000	2000
Grinding table (mm)	200	200	605	605	605	605	470	605	605	605	605
Machine height (mm)	1,390	1,390	1000	1000	1000	1000	1000	1000	1000	1000	1000
Machine length (mm)	680	680	1025	1025	1025	1025	1025	1025	1025	1025	1025
Machine width (mm)	330	330	500	500	500	500	600	500	500	600	600
Motor (HP)	2	2	4	4	4	4	4.1	5	5	5	5
Net weight (kg)	30	30	70	84	76	90	85	86	100	100	114
Number of spindle speeds	1	1	1	1	1	1	1	1	1	1	1
Rpm	2800 / 3300	2800 / 3300	2800 / 3300	2800 / 3300	2800 / 3300	2800 / 3300	2800 / 3300	2800 / 3300	3000	2800 / 3300	2800 / 3300
Voltage	400V, 50 Hz, 3-Phase	400V, 50 Hz, 3-Phase	400V, 50 Hz, 3-Phase	400V, 50 Hz, 3-Phase	220V, 50 Hz, 1-Phase	400V, 50 Hz, 3-Phase	400V, 50 Hz, 3-Phase	400V, 50 Hz, 3-Phase	400V, 50 Hz, 3-Phase	400V, 50 Hz, 3-Phase	400V, 50 Hz, 3-Phase
Wheel size, Contact wheel (ø mm)	200 x 50 x 19	200 x 50 x 19	200 x 50 x 42	200 x 50 x 42	200 x 75 x 42	200 x 75 x 42	200 x 75 x 20	200 x 100 x 42	200 x 100 x 42	200 x 150 x 42	200 x 150 x 42
Features											
EU Built (Denmark)	•	•	•	•	•	•	•	•	•	•	•
CE Certified	•	•	•	•	•	•	•	•	•	•	•
Exhaust system		•		•		•	•	•	•		•
With extra long grinding surface							•				
Separate emergency stop	•	•	•	•	•	•	•	•	•	•	•
Motor Brake	•	•	•	•	•	•	•	•	•	•	•
Quick Adjust	•	•	•	•	•	•	•	•	•	•	•
Quick belt change - Tool-less	•	•	•	•	•	•	•	•	•	•	•
5-year Motor Guarantee	•	•	•	•	•	•	•	•	•	•	•
Safety Features (Optimal)	•	•	•	•	•	•	•	•	•	•	•
											