

Press	PPCD-25	PPCD-50	PPCD-80	PPCD-100	PPCD-150
Reference Number	10100	10101	10102	10103	10104
Technical specifications					
Force [tn]:	25	50	80	100	150
Motor power [kW]:	2	4	4	6	8
Throat depth [mm]:	250	265	290	325	375
Working speed [mm/s]:	3	6	4	5	4
Approaching speed [mm/s]:	21	31	19	21	20
Return speed [mm/s]:	28	42	28	32	30
Maximum pressure [bar]:	160	320	320	320	320
Piston stroke [mm]:	250	250	250	250	250
Lower table [mm]:	400 x 400	450 x 450	500 x 500	550 x 550	650 x 650
Max. Vertical Daylight [mm]:	400	400	400	400	400
Working height [mm]:	850	850	850	900	950
Length x Width x Height [mm]:	960	1170	1330	1470	1660
Width [mm]:	740	740	780	850	900
Height [mm]:	2090	2080	2090	2155	2295
Weight [kg]:	950	1480	1750	2500	3750
Features					
Side Protection Screens:	Yes	Yes	Yes	Yes	Yes
T-Grooves (Lower Bolster Table):	Yes	Yes	Yes	Yes	Yes
Cylinder with threaded end:	Yes	Yes	Yes	Yes	Yes
Cylinder stroke adjustment:	EoS Switch	EoS Switch	EoS Switch	EoS Switch	EoS Switch
Manual/Semi-Auto Work Mode:	Yes	Yes	Yes	Yes	Yes
Cylinder speeds:	2	2	2	2	2
Pressure Switch Manometer:	Yes	Yes	Yes	Yes	Yes
Push Button (2 Hands):	Yes	Yes	Yes	Yes	Yes



PPCD Series

- 25, 50, 80, 100, 150 Tons
- Upper Ram that is Threaded
- Bolster Table (Bottom with T-Slots)
- Palm Button Operation