

Press	PPC-28	PPCM-50	PPCM-80	PPCM-100	PPCM-150
Reference Number	10010	10110	10115	10120	10125
Technical specifications					
Force [tn]:	28	50	80	100	150
Motor power [kW]:	4	4	6	8	8
Throat depth [mm]:	225	265	290	325	375
Working speed [mm/s]:	2 to 9.8	6,3	6	6	4
Approaching speed [mm/s]:		32	25	31	20
Return speed [mm/s]:	20	42	36	48	31
Maximum pressure [bar]:	320	320	320	320	320
Piston stroke [mm]:	150	250	250	250	250
Guides diameter [mm]:		50	50	50	50
Lower table [mm]:	325 x 300	700 x 450	700 x 500	800 x 550	900 x 650
Upper table [mm]:	N/A	550 x 300	600 x 350	650 x 400	700 x 450
Max. Vertical Daylight [mm]:	250	400	400	400	400
Working height [mm]:		850	850	900	950
Length x Widht x Height [mm]:	600 x 550 x 2000	1290 x 1160 x 2285	1460 x 1210 x 2090	1590 x 1240 x 2250	1750 x 1330 x 2395
Features					
Upper / Lower Table:	No / Yes	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes
Side Protection Screens:	No	Yes	Yes	Yes	Yes
Light Curtains Level 4:	No	Yes	Yes	Yes	Yes
Working Table T-Grooves:	No	DIN-650	DIN-650	DIN-650	DIN-650
Cylinder stroke adjustment:	NC Controlled	EoS Switch	EoS Switch	EoS Switch	EoS Switch
Cylinder speeds:	Variable	2	2	2	2
Pressure Switch Manometer:	N/A	Yes	Yes	Yes	Yes
Foot Pedal Operation:	Yes	Yes	Yes	Yes	Yes



PPCM Series

- 28, 50, 80, 100, 150 Tons
- Upper Slide Table
- Lower Bolster Table
- DIN 650 T-Slots
- Foot Pedal Operation