

	SB 30	SB 30 AUT	SB 30K	SB 30K AUT	SB 40	SB 40 AUT	SB 40K	SB 40K AUT	45G AUT
Article number	130601000	130601050	130601001	1306901051	140603000	140603050	140303001	140603051	100729001

Technical Specifications

Drive Mechanism	Gear Head	Gear Head	Gear Head	Gear Head	Gear Head	Gear Head	Gear Head	Gear Head	Gear Head
Automatic Feed	No	Yes	No	Yes	No	Yes	No	Yes	Yes
Max. drilling capacity	32 mm	32 mm	32 mm	32 mm	42 mm	42 mm	42 mm	42 mm	40 mm
Max. spindle travel	150 mm	150 mm	150 mm	150 mm	150 mm	150 mm	150 mm	150 mm	
Tapping Capacity	M16	M16	M16	M16	M16	M16	M16	M16	M22
Throat Depth									
Drill chuck	MT3	MT3	MT3	MT3	MT4	MT4	MT4	MT4	MT4
Column Diameter	102 mm	102 mm	102 mm	102 mm	120 mm	120 mm	120 mm	120 mm	115 mm
Size of table	405 x 505 mm	405 x 505 mm	190 x 600 mm	190 x 600 mm	405 x 505 mm	405 x 505 mm	300 x 600 mm	300 x 600 mm	555 x 495 mm
Table to Spindle Distance	915 mm	915 mm	915 mm	915 mm	915 mm	915 mm	915 mm	915 mm	470 mm
Base to Spindle Distance	285 mm	285 mm	285 mm	285 mm	350 mm	350 mm	350 mm	350 mm	260 mm
RPM	75 to 3140	75 to 3140	75 to 3140	75 to 3140	75 to 3140	75 to 3140	75 to 3140	75 to 3140	50 x 2500
Height	1730 mm	1730 mm	1730 mm	1730 mm	1800 mm	1800 mm	1800 mm	1800 mm	1960 mm
Number of Speeds - Spindle	8	8	8	8	8	8	8	8	12
Number of Speeds - Motor	2	2	2	2	2	2	2	2	--
Motor	1.5 Hp	1.5 Hp	1.5 Hp	1.5 Hp	2.3 Hp	2.3 Hp	2.3 Hp	2.3 Hp	1.5 Hp
Power Requirement	400V, 50Hz, 3-Phase	400V, 50Hz, 3-Phase	400V, 50Hz, 3-Phase	400V, 50Hz, 3-Phase	400V, 50Hz, 3-Phase	400V, 50Hz, 3-Phase	400V, 50Hz, 3-Phase	400V, 50Hz, 3-Phase	400V, 50Hz, 3-Phase
Weight	200 Kg	205 Kg	260 Kg	260 Kg	260 Kg	260 Kg	260 Kg	260 Kg	330 Kg