

SERIE V-VP

PROFESSIONAL

- Manual feed (serie V.35) - automatic feed (VP.35)
- V-belt drive
- Electronic variator and speed digital reader
- IR/RS manual tapping system



Standard equipment

- Adjustable depth end
- Tool ejector
- Belt cover with stop micro
- Emergency push button
- Turning sense selector
- Electrical equipment at low voltage
- Drill guard with stop micro
- Fixed table
- CE norms



VP.35

Extra Equipment

| | CODE |
|---|-------|
| L - LIGHTING EQUIPMENT | 20010 |
| MGI - ROTATING AND TILTING TABLE | 30084 |
| MGM - REVERSIBLE ROTATING TABLE WITH VICE | 20087 |
| ERB - COOLANT EQUIPMENT IN THE BASE | 91118 |

Characteristics

| | V.35 | VP.35 |
|--|--|-------------------------------------|
| DRILLING CAPACITY IN STEEL OF 70 Kg. (mm) | 35 | 35 |
| TAPPING CAPACITY IN STEEL OF 70 Kg. | M27 | M27 |
| TRANSMISSION | ELECTRONIC BY SPEED VARIATOR AND BELTS | |
| SPEED NUMBER AND RANGE 50 HZ. | VARIABLE 100-2000 rpm. | |
| FEED | MANUAL | AUTOMATIC |
| NUMBER AND FEED NUMBER | - | (3) 0,10-0,20-0,30 |
| CLUTCH | - | MECÁNICO |
| MAIN MOTOR POWER - 750/1500 rpm. | 4 HP | 4 HP |
| SPINDLE CONE | MT4 | MT4 |
| SPINDLE STROKE | 150 mm | 150 mm |
| DISTANCE SPINDLE-COLUMN | 300 mm | 300 mm |
| DISTANCE SPINDLE-TABLE | Min. 90 mm/ Max. 890 mm | Min. 90 mm/ Max. 890 mm |
| DISTANCE SPINDLE-BASE | 1250 mm. | 1250 mm. |
| COLUMN DIAMETER | Ø125 mm. | Ø125 mm. |
| DIMENSIONS OF THE TABLE (WITH 2 T SLOTS) | 400x420 mm. | 400x420 mm. |
| DIMENSIONS OF THE BASE WITHOUT T SLOTS (WITHOUT COOLANT) | 400x655 mm | 400x655 mm |
| DIMENSIONS OF THE BASE WITH 2 T SLOTS (WITH COOLANT) | 492x655 mm | 492x655 mm |
| WEIGHT: NET / GROSS Kg. | 345 / 395 Kg. | 360 / 410 Kg. |
| PACKAGING DIMENSIONS AND VOLUME | 2,3x0,60x1,1 m – 1,5 m ³ | 2,3x0,60x1,1 m – 1,5 m ³ |

Dimensiones

